

# INSTALLATION INSTRUCTION FOR 5328-577

**WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER .**  
**AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.**

READ AND SAVE THESE INSTRUCTIONS

## PREPARATION

1. Shut off the power at the circuit breaker box. If necessary, remove the old fixture and all mounting hardware from junction box.
2. Carefully unpack your new fixture and lay out all the parts on a clear area. Take care not to loose any small parts necessary for installation.

## ASSEMBLING THE FIXTURE (Fig. 1)

3. Spread the arms (J) so that the arms (J) are at equal distance from each other.
4. Secure the part (I) of the decorative arms (F) to the canopy (D) with the screws (G), then secure the part (II) of the decorative arms (F) to the coupling (I) with the screws (G).
5. Thread the nut (L) onto the nipple (M), then thread the nipple (M) into the coupling (K) and tighten with the nut (L).
6. Install the light bulb(s) in accordance with the fixture's specifications (**DO NOT EXCEED THE MAXIMUM WATTAGE!**) (**NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!**)
7. Slide the glass (N), plastic washer (O) and iron washer (P) over the nipple (M) and secure with the nut (Q).
8. Slide the cap (R) over the nipple (M), and secure with the finial (S).

## MOUNTING THE FIXTURE (Fig.1)

9. Thread the two mounting screws (A) (Size: #8-32\*1.1"L) part way into the crossbar (B). Secure the crossbar (B) to junction box (not provided) with the junction box screws (C) (Size: #8-32\*0.6"L) through the slotted holes in mounting bar (B). The side of the mounting bar (B) marked "GND" must face out.

## CONNECTING THE WIRES (Fig. 2)

10. Connect the fixture wires to the junction box wires as shown in Fig. 2, making sure all wire connectors are secured. If your outlet box has a ground wire (green or bare copper) connect the fixture's ground wire to it. Otherwise, connect the fixture's ground wire directly to the mounting plate using the green screw provided. After the wires are connected, tuck them neatly inside the junction box.

## COMPLETING THE INSTALLATION (Fig. 1)

12. Raise the canopy (D) allowing for the mounting screws (A) to protrude through the holes on the canopy (D), then secure with the finials (E).

Return the power to the junction box and test the fixture. Your installation is now complete.



